

BESTWAY

BCE.01.1

CASTER ESSENTIALS




About Bestway Casters:

Bestway Casters & Wheels Ltd. has kept Industry rolling for over 25 years. As a full line caster and wheel manufacturer, Bestway is your number one source for everything from light-duty furniture casters to super heavy-duty industrial models. Virtually all of our industrial casters are North American made ensuring the highest quality, speedy delivery and competitive pricing. And since we are the manufacturer, not just an importer or distributor, we can fully customize our casters to suit any specific application you may have.

This "Caster Essentials" Catalogue shows just a very limited selection of the more common caster and wheel combinations available to our customers. Many more caster and wheel types are available from our factory, so please give us a call if you cannot find what you are looking for.

At Bestway we pride ourselves on our reputation for quality products and exceptional service. Give us a call and discover the Bestway advantage for yourself!



LP/LPR SERIES

Wheel Diam.	OAH	Swiv. Rad.
3"	4"	3-1/8"
4"	5"	3-1/4"
5"	6"	4"

This versatile double ball caster is ideal for light loads where ease of movement is required. Bright zinc plating assures long life and dependability.

LP/BR-5125-UN-BB

Also available in Stainless Steel

230 lbs. Maximum Capacity

Top Plate: 2-5/8" x 3-3/4" Mounting Holes: 1-3/4" x 2-7/8" - 3" BHS, 5/16" Hole clearance

Swivel	Rigid	Width	Wheel Type	Capacity (lbs.)	Bearing Type
3" Diameter Wheels					
LP-3125-MR	LPR-3125-MR	1-1/4"	Multi-Purpose Rubber	210	Plain
LP-3125-EL-BB	LPR-3125-EL-BB	1-1/4"	Eliminator Grey	200	Ball Bearing
LP-3125-NL	LPR-3125-NL	1-1/4"	Ny-Lite	230	Plain
4" Diameter Wheels					
LP-4125-NL	LPR-4125-NL	1-1/4"	Ny-Lite	230	Plain
LP-4125-EL-BB	LPR-4125-EL-BB	1-1/4"	Eliminator Grey	220	Ball Bearing
LP-4138-MR	LPR-4138-MR	1-3/8"	Multi-Purpose Rubber	230	Plain
5" Diameter Wheels					
LP-5125-NL	LPR-5125-NL	1-1/4"	Ny-Lite	230	Plain
LP-5125-EL-BB	LPR-5125-EL-BB	1-1/4"	Eliminator Grey	220	Ball Bearing
LP-5138-MR	LPR-5138-MR	1-3/8"	Multi-Purpose Rubber	230	Plain

Options: (1) For side pedal brake on swivels only. Add code 'BR' to model number (eg. LP/BR-5125-NL)

GP/GPR SERIES (Formerly GN & GR)

Wheel Diam.	OAH	Swiv. Rad.
3"	4-1/16"	2-11/16"
4"	5-1/16"	3-1/2"
5"	6-1/8"	4-1/8"
6"	7"	4-5/8"

This Medium Duty caster is truly a beautiful product. Swivels feature precision formed double ball raceways and head seals. The optional "Total Lock Brake" locks both the wheel and swivel with one press of the pedal.

GP/TLB-3150C-ES-HRB



500 lbs. Maximum Capacity

Top Plate: 3-3/8" x 4-1/8" Mounting Holes: 2-1/8" x 2-7/8" or 2-5/8" x 3-3/8" BHS, 5/16" Hole clearance

Swivel	Rigid	Width	Wheel Type	Capacity (lbs.)	Bearing Type
3" Diameter Wheels					
GP-3125-UN-BB	GPR-3125-UN-BB	1-1/4"	Star-Tech Urethane	250	Ball Bearing
GP-3150-BAL-RB	GPR-3150-BAL-RB	1-1/2"	Phenolic	300	Roller
GP-080-HTM-HL	GPR-080-HTM-HL	1-1/4"	Hi-Temp Monolithic	220	Hi-Lex
4" Diameter Wheels					
GP-4150-BAL-RB	GPR-4150-BAL-RB	1-1/2"	Phenolic	350	Roller
GP-4150-UN-RB	GPR-4150-UN-RB	1-1/2"	Star-Tech Urethane	350	Roller
GP-100-HTM-HL	GPR-100-HTM-HL	1-1/4"	Hi-Temp Monolithic	275	Hi-Lex
5" Diameter Wheels					
GP-5150-BAL-RB	GPR-5150-BAL-RB	1-1/2"	Phenolic	450	Roller
GP-5150-UN-RB	GPR-5150-UN-RB	1-1/2"	Star-Tech Urethane	450	Roller
6" Diameter Wheels					
GP-6150-BAL-RB	GPR-6150-BAL-RB	1-1/2"	Phenolic	500	Roller
GP-6150-UN-RB	GPR-6150-UN-RB	1-1/2"	Star-Tech Urethane	500	Roller

Options: (1) Total Lock Brake available on swivels only. Add code 'TLB' to model number (eg. GP/TLB-5150-BAL-RB)

About Our Patented Double Ball Kingboltless Casters™: Canada #2179802 USA #5983451

Bestway has revolutionized the Caster Industry with the introduction of our PATENTED Double Ball Kingboltless Casters™! These casters replace traditional nut & bolt or riveted pins with a pair of precision machined and hardened raceways welded to the top plate. Since there is no kingpin to bend or break, these casters feature superior capacity and durability versus traditional casters. This design is ideal for towline or shock load applications and unlike inferior single race models, our PATENTED Double Ball Kingboltless Casters™ have one raceway to handle the load and another to take the swivel action, making the caster much easier to operate.

Bestway is your guarantee of quality since all of our PATENTED Double Ball Kingboltless Casters™ are North American made, ensuring the highest quality construction, quick delivery and full customization available. Don't be satisfied with inferior imitations or imports.



LS/LSR SERIES

Wheel Diam.	OAH	Swiv. Rad.
6"	7-1/2"	5-1/2"
8"	10-1/8"	6-1/2"
10"	11-1/2"	7-3/4"
12"	13-1/2"	9"

Using our PATENTED Double Ball Kingboltless design, the LS Series offers higher capacities and greater durability than traditional forged head designs and is ideal for towline and shock load applications. The 4-1/2" diameter precision machined and hardened head incorporates over fifty 5/16" diameter ball bearings in 2 raceways for top performance.

Also available in Stainless Steel **LS-6250L-DU-RB**

3,500 lbs. Maximum Capacity Top Plate: 4-1/2" x 6-1/4" Mounting Holes: 2-7/16" x 4-15/16" or 3-3/8" x 5-1/4" BHS, 1/2" Hole clearance

Swivel	Rigid	Width	Wheel Type	Capacity (lbs.)	Bearing Type
6" Diameter Wheels					
LS-6300-BAL-RB	LSR-6300-BAL-RB	3"	Phenolic	2000	Roller
LS-6300-DU-RB	LSR-6300-DU-RB	3"	Ductile Iron	3500	Roller
8" Diameter Wheels					
LS-8300-BAL-RB	LSR-8300-BAL-RB	3"	Phenolic	2500	Roller
LS-8300-DU-RB	LSR-8300-DU-RB	3"	Ductile Iron	3500	Roller
10" Diameter Wheels					
LS-10300-BAL-RB	LSR-10300-BAL-RB	3"	Phenolic	2500	Roller
LS-10300-DU-RB	LSR-10300-DU-RB	3"	Ductile Iron	3500	Roller
12" Diameter Wheels					
LS-12300-BAL-RB	LSR-12300-BAL-RB	3"	Phenolic	3500	Roller
LS-12300-DU-RB	LSR-12300-DU-RB	3"	Ductile Iron	3500	Roller

Options: (1) Pedal Brake available on swivels and rigids. Add code 'BR' to model number (eg. LS/BR-8300-DU-RB)

KP/KPR SERIES

Wheel Diam.	OAH	Swiv. Rad.
6"	8-1/2"	4-3/4"
8"	10-1/2"	6-3/16"
10"	12-1/2"	7-11/16"
12"	15-1/2"	9-5/8"

Where high capacity and durability are a must - the KP Series are the casters for you! Using our PATENTED Double Ball Kingboltless design, these casters offer unmatched performance. The super-strength 6-1/2" diameter swivel head is locked together by over fifty 1/2" diameter balls and is securely welded to the 1/2" thick Top Plate.


KP-6400-DU-TB



10,000 lbs. Maximum Capacity Top Plate: 6-1/4" x 7-1/2" Mounting Holes: 4-1/2" x 6" or 4-1/8" x 6-1/8" BHS, 1/2" Hole clearance

Swivel	Rigid	Width	Wheel Type	Capacity (lbs.)	Bearing Type
6" Diameter Wheels					
KP-6300-DU-RB	KPR-6300-DU-RB	3"	Ductile Iron	6000	Roller
CONSULT FACTORY	KPR-6300-VGD-RB	3"	V-Groove Ductile	5000	Roller
KP-6400-DU-TB	KPR-6400-DU-TB	4"	Ductile Iron	10000	Tapered
KP-6400-UC-TB	KPR-6400-UC-TB	4"	Urethane on Cast	5750	Tapered
8" Diameter Wheels					
KP-8300-DU-RB	KPR-8300-DU-RB	3"	Ductile Iron	6000	Roller
CONSULT FACTORY	KPR-8300-VGD-RB	3"	V-Groove Ductile	5000	Roller
KP-8400-DU-TB	KPR-8400-DU-TB	4"	Ductile Iron	10000	Tapered
KP-8400-UC-TB	KPR-8400-UC-TB	4"	Urethane on Cast	5750	Tapered
10" Diameter Wheels					
KP-10300-DU-RB	KPR-10300-DU-RB	3"	Ductile Iron	6000	Roller
CONSULT FACTORY	KPR-10300-VGD-RB	3"	V-Groove Ductile	5000	Roller
KP-10400-DU-TB	KPR-10400-DU-TB	4"	Ductile Iron	10000	Tapered
KP-10400-UC-TB	KPR-10400-UC-TB	4"	Urethane on Cast	5750	Tapered
12" Diameter Wheels					
KP-12300-DU-RB	KPR-12300-DU-RB	3"	Ductile Iron	6000	Roller
CONSULT FACTORY	KPR-12300-VGD-RB	3"	V-Groove Ductile	5000	Roller
KP-12400-DU-TB	KPR-12400-DU-TB	4"	Ductile Iron	10000	Tapered
KP-12400-UC-TB	KPR-12400-UC-TB	4"	Urethane on Cast	5750	Tapered

Options: (1) Poly Cam Brake available on swivels and rigids. Add code 'PCB' to model number (eg. KP/PCB-8300-DU-RB)
 (2) T-Handle Brake available on swivels and rigids. Add code 'TBR' to model number (eg. KPR/TBR-10300-VGD-RB)
 (3) Four Position Swivel Lock. Add code '4SL' to model number (eg. KP/4SL-8400-DU-TB)



IH/IHR SERIES

Wheel Diam.	OAH	Swiv. Rad.
6"	9"	5-3/16"
8"	11"	6-3/16"
10"	13"	7-9/16"
12"	15"	9-1/8"

This super heavy-duty caster featuring our PATENTED Double Ball Kingboltless technology can't be beat! An extremely high-strength 7-1/2" diameter swivel head features two precision machined and hardened raceways locked together by over fifty 5/8" diameter ball bearings. The 1/2" thick top plate and 1-1/4" axle make it the best heavy-duty towable caster anywhere!

IH-10400-UC-TB

17,000 lbs. Maximum Capacity **Top Plate: 8-1/2" x 8-1/2"** **Mounting Holes: 7" x 7"** **Bolt Hole Spacing, 5/8"** **Hole clearance**

Swivel	Rigid	Width	Wheel Type	Capacity (lbs.)	Bearing Type
6" Diameter Wheels					
IH-6400-DU-TB	IHR-6400-DU-TB	4"	Ductile Iron	17000	Tapered
IH-6400-UDU-TB	IHR-6400-UDU-TB	4"	Urethane on Ductile	12000	Tapered
8" Diameter Wheels					
IH-8400-DU-TB	IHR-8400-DU-TB	4"	Ductile Iron	17000	Tapered
IH-8400-UDU-TB	IHR-8400-UDU-TB	4"	Urethane on Ductile	12000	Tapered
10" Diameter Wheels					
IH-10400-DU-TB	IHR-10400-DU-TB	4"	Ductile Iron	17000	Tapered
IH-10400-UDU-TB	IHR-10400-UDU-TB	4"	Urethane on Ductile	12000	Tapered
12" Diameter Wheels					
IH-12400-DU-TB	IHR-12400-DU-TB	4"	Ductile Iron	17000	Tapered
IH-12400-UDU-TB	IHR-12400-UDU-TB	4"	Urethane on Ductile	12000	Tapered

Options: (1) Poly Cam Brake available on swivels and rigids. Add code 'PCB' to model number (eg. IH/PCB-8400-UDU-TB)
 (2) T-Handle Brake available on swivels and rigids. Add code 'TBR' to model number (eg. IH/TBR-10400-DU-TB)
 (3) Four Position Swivel Lock. Add code '4SL' to model number (eg. IH/4SL-6400-DU-TB)

RT/RTR SERIES (Formerly RTP & RTPR)

Wheel Diam.	OAH	Swiv. Rad.
4"	5-5/8"	3-9/16"
5"	6-1/2"	4-1/4"
6"	7-1/2"	5"
8"	9-1/2"	6-1/2"

The RT Series uses the same high quality construction as our signature "Bestway" Series in a stem caster. Our wide selection of standard and custom stems mean that this caster can be mounted in virtually any application. Made here in North America so you can be assured of the finest quality and speedy delivery at competitive prices.



Also available in Stainless Steel

RTR-5200-BAL-RB

700 lbs. Maximum Capacity

Mounting: Standard and Custom Stems Available (Consult Factory)

Swivel	Rigid	Width	Wheel Type	Capacity (lbs.)	Bearing Type
4" Diameter Wheels					
RT-4150-UC-RB	RTR-4150-UC-RB	1-1/2"	Urethane on Cast	400	Roller
RT-4200-EL-RB	RTR-4200-EL-RB	2"	Eliminator Grey	400	Roller
RT-4200-NL-RB	RTR-4200-NL-RB	2"	Ny-Lite	400	Roller
5" Diameter Wheels					
RT-5150-UC-RB	RTR-5150-UC-RB	1-1/2"	Urethane on Cast	500	Roller
RT-5200-EL-RB	RTR-5200-EL-RB	2"	Eliminator Grey	500	Roller
RT-5200-NL-RB	RTR-5200-NL-RB	2"	Ny-Lite	600	Roller
6" Diameter Wheels					
RT-6150-UC-RB	RTR-6150-UC-RB	1-1/2"	Urethane on Cast	500	Roller
RT-6200-EL-RB	RTR-6200-EL-RB	2"	Eliminator Grey	600	Roller
RT-6200-NL-RB	RTR-6200-NL-RB	2"	Ny-Lite	600	Roller
8" Diameter Wheels					
RT-8200-EL-RB	RTR-8200-EL-RB	2"	Eliminator Grey	700	Roller
RT-8200-NL-RB	RTR-8200-NL-RB	2"	Ny-Lite	700	Roller

Options: (1) Pedal Brake available on swivels and rigids. Add code 'BR' to model number (eg. RT/BR-8200-EL-RB)

Sample Standard Stem Model Numbers

RT Stem: .845" X 2-1/2" SC
 RT Stem: 7/8" X 2" SC
 RT Stem: 3/4"-10 X 4" TS
 RT Stem: 1"-8 X 4" TS

Stem Type Material

Stem & Circlip Zinc Plated
 Stem & Circlip Zinc Plated
 Threaded Stem Steel
 Threaded Stem Steel

Please call for a complete list of stems.

Note: Bestway Casters reserves the right to change specifications without notice.

BESTWAY CASTERS & WHEELS LTD.

1166 Gorham Street, Units 5-8, Newmarket, Ontario Canada L3Y 7V1
 Local: (905) 853-3412 Toll Free (Canada): (877) 828-0451
 US Customers: (800) 463-4193 Quebec: (514) 855-1234
 Fax: (905) 853-7310 E-Mail: sales@BestwayCasters.com

Or visit our website at: www.BestwayCasters.com

CALL FOR THE DISTRIBUTOR NEAREST YOU